



Suction Regulator

Model: EcoSafe400 (0-400 mmHg)

Model: EcoSafe760 (0-760 mmHg)

Acare's EcoSafe Suction Regulator provides reliable, safe suctioning in continuous flow suction procedures.

The unit is specifically designed to provide high flow rates and minimal restriction in the sickroom or operating room where requires high level suction use for patients. The variety of inlet connection can be selected according to the couplers on the hospital's wall. It's featured with easy maintenance.

Features

- Accurate suction control within range
- Quick switch for Reg/Off/Full Vacuum
- Clear Analog Display in the pressure gauge
- Simplified internal mechanical design for easy maintenance
- Nice outlook with durable plastic case
- Large control knob for easy setting
- Removable back plate and gasket for easy cleaning
- Available in a variety of inlet connections

Outlet connection

- 1/8" Female NPT
- DISS

Inlet connection



- Ohmeda
- Ohio



- Chemetron



- Oxequip



- Puritan-Bennett



- DISS



- Kawasaki



- MK-II

Safety Trap



Safety Traps are recommended to use for protecting regulators and preventing accidental overflow.

- Trap fitting connection
- 1/8" Male NPT
 - DISS

Reusable Jar

- Reusable Jar fitting connection
- Brass adapter
 - DISS



- MK-IV



EcoSafe760



EcoSafe400



Wel-Tech Gas Equipment Sdn. Bhd.

No. 17, Jalan Selampit 21, Taman Klang Jaya, 41200 Klang, Selangor, Malaysia.
Tel : (603) 3323 1979 Fax: (603) 3323 5980 Email: weltechgas@gmail.com